

## **RM-7 and RM-7N Districts Schedules**

### **1 Intent**

The intent of this schedule is to encourage development of ground-oriented stacked townhouses or rowhouses, while continuing to permit lower intensity development. Siting and massing of new development are intended to be compatible with, but not the same as, pre-existing single family development. Secondary suites and lock-off units are permitted, within limits, to provide flexible housing choices. Retention of character buildings and high quality design and livability standards are encouraged for new development. The RM-7N District differs from the RM-7 District, because it requires noise mitigation for dwelling units fronting arterial streets.

Individual one-family dwellings and one-family dwellings with a secondary suite (with or without a laneway house) are permitted uses; however, if developed as the only principal building on a site, these uses are regulated by the RS-1 District Schedule. In all other cases, this schedule will apply.

### **2 Outright Approval Uses**

2.1 Subject to all other provisions of this by-law and to compliance with the regulations of this schedule, the uses listed in section 2.2 are permitted in these districts and will be issued a permit.

#### **2.2 Uses**

- 2.2.A
- Accessory Buildings customarily ancillary to any of the uses listed in this schedule, except for accessory buildings ancillary to multiple dwelling and freehold rowhouse use, provided that:
    - (a) no accessory building exceeds 3.7 m in height, measured to the highest point of the roof if a flat roof, to the deck line of a mansard roof, or to the mean height of the level between the eaves and the ridge of a gable, hip or gambrel roof, except that no portion of an accessory building may exceed 4.6 m in height;
    - (b) all accessory buildings are located:
      - (i) within 7.9 m of the ultimate rear property line, and
      - (ii) no less than 3.6 m from the ultimate centre line of any rear or flanking lane and 1.5 m from a flanking street;
    - (c) the total floor area of all accessory buildings, measured to the extreme outer limits of the building, is not greater than 48 m<sup>2</sup>;
    - (d) not more than 80% of the width of the site at the rear property line is occupied by accessory buildings;
    - (e) no accessory building is closer than 3.7 m to any residential dwelling; and
    - (f) roof decks and sun decks are not located on an accessory building.
  - Accessory Uses customarily ancillary to any of the uses listed in this section, provided that accessory parking spaces must comply with the provisions of section 2.2.A (b) of this schedule.

2.2.DW [Dwelling]

- Multiple Conversion Dwelling, provided that:
  - (a) no additions are permitted;
  - (b) no housekeeping or sleeping units are created;

- (c) there are no more than 2 dwelling units;
- (d) the development complies with section 4.8 of this schedule; and
- (e) no development permit will be issued until the requisite permits required by other by-laws that relate to design, construction and safety of buildings are issuable.

- One-Family Dwelling which complies with the current RS-1 District Schedule, provided that the one-family dwelling is the only principal building on the site.
- Two-Family Dwelling.

2.2.I [Institutional]

- Community Care Facility – Class A, subject to the regulations and relaxations that apply to a one-family dwelling.

### **3 Conditional Approval Uses**

3.1 Subject to all other provisions of this by-law, the Director of Planning may approve any of the uses listed in section 3.2 of this schedule, with or without conditions, provided that the Director of Planning first considers:

- (a) the intent of this schedule and all applicable Council policies and guidelines; and
- (b) the submission of any advisory group, property owner or tenant.

### **3.2 Uses**

- 3.2.A
- Accessory Buildings not provided for in section 2.2.A of this schedule and customarily ancillary to any of the uses listed in this schedule, provided that for multiple dwelling and freehold rowhouse,
    - (a) no accessory building exceeds 3.7 m in height, measured to the highest point of the roof if a flat roof, to the deck line of a mansard roof, or to the mean height of the level between the eaves and the ridge of a gable, hip or gambrel roof, except that no portion of an accessory building may exceed 4.6 m in height;
    - (b) all accessory buildings are located:
      - (i) within 7.9 m of the ultimate rear property line, and
      - (ii) no less than 3.6 m from the ultimate centre line of any rear or flanking lane, and 1.5 m from a flanking street;
    - (c) the total floor area of all accessory buildings, measured to the extreme outer limits of the building, is not greater than 48 m<sup>2</sup>, except that:
      - (i) the Director of Planning may increase the total floor area of all accessory buildings to a maximum of 24 m<sup>2</sup> for each dwelling unit, not including lock-off units, if the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines;
    - (d) not more than 30% of the width of the site at the rear property line is occupied by accessory buildings, except that the Director of Planning may increase the amount of the width of the site at the rear property line that may be occupied by accessory buildings to a maximum of 80%, if the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines;
    - (e) no accessory building is closer than 3.7 m to any residential dwelling; and
    - (f) roof decks and sun decks are not located on an accessory building.
  - Accessory Uses customarily ancillary to any of the uses listed in this section.

- 3.2.C [Cultural and Recreational]
- Club.
  - Community Centre or Neighbourhood House.
  - Library in conjunction with a Community Centre.
  - Park or Playground.
- 3.2.D • Deposition or extraction of material, which alters the configuration of the land.
- 3.2.DW [Dwelling]
- Dwelling Units, up to a maximum of two, in conjunction with a Neighbourhood Grocery Store existing as of July 29, 1980, subject to section 11.16 of this by-law.
  - Freehold rowhouse, subject to section 11.25 of this by-law.
  - Infill One-Family Dwelling, provided that the maximum number of dwelling units on the site is three, and:
    - (a) it is in conjunction with the retention of a building existing on the site prior to January 1, 1940; or
    - (b) the site meets the following criteria:
      - (i) the rear or side property line of the site must abut a park or school site, with or without the intervention of a lane, or
      - (ii) the site must be a corner site, or
      - (iii) the lot depth must be more than 52 m.
  - Laneway House on a site with one principal building, subject to section 11.24 of this by-law and the RS-1 District Schedule.
  - Multiple Conversion Dwelling not provided for in section 2.2.DW of this schedule, resulting from the conversion of a building existing as of May 15, 2013, provided that:
    - (a) the Director of Planning first considers the quality and livability of the resulting units, the suitability of the building for conversion in terms of age and size and the effect of the conversion on adjacent properties;
    - (b) additions are not permitted for buildings constructed on or after January 1, 1940, except additions up to a maximum of 5 m<sup>2</sup> used as exits;
    - (c) no housekeeping or sleeping units are created; and
    - (d) there are no more than three dwelling units.
  - Multiple Dwelling.
  - One-Family Dwelling on a site with two principal buildings, in accordance with sections 4.1.1 and 4.19.1 of this schedule.
  - One-Family Dwelling with Secondary Suite on a site with one principal building, which complies with the current RS-1 District Schedule.
  - One-Family Dwelling with Secondary Suite on a site with two principal buildings, in accordance with sections 4.1.1 and 4.19.1 of this schedule.
  - Principal Dwelling Unit with Lock-off Unit, provided that:
    - (a) in multiple dwellings or freehold rowhouses, there may be one lock-off unit for every 3 principal dwelling units, except that the Director of Planning may permit a higher ratio after first considering the intent of this schedule and all applicable Council policies and guidelines.
  - Two-Family Dwelling on a site with two principal buildings, in accordance with sections 4.1.1 and 4.19.1 of this schedule.
  - Two-Family Dwelling with Secondary Suite on a site with two principal buildings, in accordance with sections 4.1.1 and 4.19.1 of this schedule.

- Two-Family Dwelling with Secondary Suite, provided that there is no more than one secondary suite for each dwelling unit.
- Seniors Supportive or Assisted Housing, subject to section 11.17 of this by-law.

### 3.2.I [Institutional]

- Ambulance Station.
- Child Day Care Facility.
- Church, subject to section 11.7 of this by-law.
- Community Care Facility – Class B, subject to section 11.17 of this by-law.
- Group Residence, subject to section 11.17 of this by-law.
- Hospital, subject to section 11.9 of this by-law.
- Public Authority Use essential in this district.
- School - Elementary or Secondary, subject to section 11.8 of this by-law.
- Social Service Centre.

### 3.2.R [Retail]

- Farmers' Market, subject to section 11.21 of this by-law, and to compatibility with nearby sites, parking, traffic, noise, hours of operation, size of facility, and pedestrian amenity.
- Neighbourhood Grocery Store existing as of July 29, 1980, subject to section 11.16 of this by-law.

### 3.2.S [Service]

- Bed and Breakfast Accommodation, subject to section 11.4 of this by-law.

### 3.2.U [Utilities and Communication]

- Public Utility.

## **4 Regulations**

All approved uses are subject to the following regulations, except for:

- (a) One-Family Dwelling and One-Family Dwelling with Secondary Suite, as the only principal building on the site, which are regulated by the RS-1 District Schedule; and
- (b) Laneway House, which is only permitted in combination with 4(a), and is regulated by section 11.24 of this by-law.

### **4.1 Site Area**

#### 4.1.1 The minimum site area for:

- (a) a two-family dwelling;
- (b) a two-family dwelling with secondary suite;
- (c) a multiple conversion dwelling with more than two dwelling units;
- (d) any of the above noted uses or a one-family dwelling or one-family dwelling with secondary suite, in combination with an infill one-family dwelling or another principal building; or
- (e) a multiple dwelling containing no more than 3 dwelling units, not including lock-off units,

is 303 m<sup>2</sup>.

#### 4.1.2 The minimum site area for a multiple dwelling containing 4 or more dwelling units, not including lock-off units, for a building containing freehold rowhouses, or for seniors supportive or assisted housing is 445 m<sup>2</sup>.

- 4.1.3 If the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines, the Director of Planning may permit a freehold rowhouse or a multiple dwelling containing 4 or more dwelling units, not including lock-off units, on a site smaller than 445 m<sup>2</sup>.

## **4.2 Frontage**

- 4.2.1 The minimum frontage for a multiple dwelling containing 4 or more dwelling units, not including lock-off units, is 12.8 m.

## **4.3 Height**

- 4.3.1 A building must not exceed 9.5 m and 2 storeys in height.
- 4.3.2 Notwithstanding section 4.3.1 of this schedule, a two-family dwelling, a two-family dwelling with secondary suite, a multiple dwelling containing no more than three units, not including lock-off units, and a freehold rowhouse must not exceed 10.7 m and 2½ storeys in height.
- 4.3.3 Notwithstanding section 4.3.1 of this schedule, the Director of Planning may permit a height increase in a multiple dwelling containing 4 or more dwelling units, not including lock-off units, to 11.5 m and a partial 3rd storey, if:
- (a) the 3rd storey, meaning the uppermost level of a building where the floor area, existing, proposed or as may be extended over open-to-below space, and having a minimum ceiling height of 1.2 m, does not exceed 60% of the storey immediately below; and
  - (b) the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.
- 4.3.4 Notwithstanding sections 4.3.1 and 4.3.2 of this schedule, where a site is encumbered by a right of way granted to the Greater Vancouver Sewerage and Drainage District, the Director of Planning may permit a height increase in a multiple dwelling containing 4 or more dwelling units, not including lock-off units, to 11.5 m and a 3rd storey, provided the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.
- 4.3.5 Notwithstanding sections 4.3.1, 4.3.2 and 4.3.3 of this schedule, the maximum building height for an infill one-family dwelling or a principal building situated in the rear yard of a site is the lesser of 7.7 m or 1½ storeys, except that the Director of Planning may increase the maximum height if the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.
- ## **4.4 Front Yard**
- 4.4.1 Front yards must have a minimum depth of 6.1 m.
- 4.4.2 Notwithstanding section 4.4.1 of this schedule, on sites less than 27.4 m in depth, front yards must have a minimum depth of 4.9 m.
- 4.4.3 Notwithstanding sections 4.4.1 and 4.4.2 of this schedule, the Director of Planning may decrease the front yard requirement for multiple dwellings and freehold rowhouses on sites less than 27.4 m in depth, provided that the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.
- 4.4.4 Covered porches complying with section 4.7.5 (h) of this schedule, may project up to 1.2 m into the required front yard.

4.4.5 For multiple dwellings, portions of basement floor area directly below covered porches may project up to 1.2 m into the required front yard.

4.4.6 Notwithstanding section 10.7.1(b) of this by-law, eaves and gutters or other projections, which in the opinion of the Director of Planning are similar, may project into the minimum front yard to a maximum of 1.0 m measured horizontally.

#### **4.5 Side Yards**

4.5.1 Side yards must have a minimum width of 1.2 m.

4.5.2 Notwithstanding section 10.7.1(b) of this by-law, eaves and gutters or other projections, which, in the opinion of the Director of Planning are similar, may project into the minimum side yard up to a maximum of 1.0 m measured horizontally, except that they must not be closer than 0.7 m to a side property line.

#### **4.6 Rear Yard – not applicable**

#### **4.7 Floor Space Ratio**

4.7.1 Floor space ratio must not exceed 0.60 for all uses, except that floor space must not exceed 0.75 for two-family dwelling and two-family dwelling with secondary suite.

4.7.2 Notwithstanding section 4.7.1 of this schedule, if the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines, and the submissions of any advisory groups, property owners or tenants, the Director of Planning may permit an increase in floor space ratio:

- (a) for multiple dwelling, freehold rowhouse or seniors supportive or assisted housing on sites that are 445 m<sup>2</sup> and larger, with a minimum frontage of 12.8 m, to a maximum of 1.20;
- (b) for multiple dwelling or seniors supportive or assisted housing on sites that are less than 445 m<sup>2</sup> in size or with a frontage less than 12.8 m, to a maximum of 0.90;
- (c) for dwelling uses on sites where buildings existing prior to January 1, 1940 are retained, to a maximum of 0.90; and
- (d) for all other dwelling uses, except two-family dwelling and two-family dwelling with secondary suite, to a maximum of 0.85.

4.7.3 Notwithstanding section 4.7.2 of this schedule, for sites where a building existing prior to January 1, 1940, is not retained, no more than 0.20 floor space ratio may be allocated to an infill one-family dwelling or to another second principal building in the rear yard of the site.

4.7.4 Computation of floor area must include:

- (a) all floors, including earthen floor, to be measured to the extreme outer limits of the building;
- (b) stairways, fire escapes, elevator shafts, and other features which the Director of Planning considers similar, measured by their gross cross-sectional areas and included in the measurements for each floor at which they are located;
- (c) where the distance from a floor located no more than 2.0 m above finished grade to the floor above, or where there is no floor above, to the top of the roof joists, exceeds 3.7 m, an amount equal to the area of the floor below the excess height, except that the Director of Planning may exclude an area designed with venting skylights, opening clerestory windows or other similar features if:
  - (i) in the opinion of the Director of Planning, the area is designed to reduce energy consumption or improve natural light and ventilation, and
  - (ii) the area excluded does not exceed 1% of the permitted floor area;

- (d) the floor area of bay windows, regardless of seat height, location in building or relationship to yard setbacks, which is greater than the product of the total floor area permitted above the basement multiplied by 0.01; and
- (e) accessory buildings, ancillary to multiple dwellings and freehold rowhouses, except accessory buildings solely designed and constructed for the purpose of bicycle storage, or otherwise excluded in accordance with section 4.7.5 (c) of this schedule.

#### 4.7.5 Computation of floor area must exclude:

- (a) open residential balconies or sun decks, and any other appurtenances which, in the opinion of the Director of Planning, are similar to the foregoing, provided that the total area of these exclusions does not exceed 12% of the permitted floor area for multiple dwelling and freehold rowhouse and 8% of the permitted floor area for all other uses;
- (b) patios and roof gardens, provided the Director of Planning first approves the design of sunroofs and walls;
- (c) for multiple dwelling and freehold rowhouse, where floors are used for:
  - (i) off-street parking and loading, those floors or portions thereof which are located below base surface, provided that the maximum exclusion for a parking space must not exceed 7.3 m in length, and
  - (ii) bicycle storage located below base surface, or, if located at or above base surface are contained in an accessory building which complies with section 3.2.A of this schedule;
- (d) for dwelling uses other than multiple dwelling and freehold rowhouse, where floors are used for off-street parking and loading, or bicycle storage in multiple conversion dwellings containing 3 or more dwelling units, or uses which, in the opinion of the Director of Planning, are similar to the foregoing:
  - (i) those floors or portions thereof not exceeding 7.3 m in length, which are located in an accessory building which complies with section 2.2.A of this schedule, or in an infill one family dwelling or principal building located within 7.9 m of the ultimate rear property line, up to a maximum of 48 m<sup>2</sup>, and
  - (ii) on sites with no developed secondary access, those floors or portions thereof not exceeding 7.3 m in length and minimum required maneuvering aisle, which are located either in a principal building, an accessory building, or an infill one-family dwelling up to a maximum area that the Director of Planning may determine, provided the Director of Planning first considers all applicable Council policies and guidelines;
- (e) for non-dwelling uses, where floors are used for off-street parking and loading, heating and mechanical equipment, or uses which, in the opinion of the Director of Planning, are similar to the foregoing, those floors or portions thereof not exceeding 7.3 m in length so used, which are located in an accessory building located within 7.9 m of the ultimate rear property line, or below base surface;
- (f) areas of undeveloped floors which are located:
  - (i) above the highest storey or half-storey and to which there is no permanent means of access other than a hatch, or
  - (ii) adjacent to a storey or half-storey with a ceiling height of less than 1.2 m;
- (g) floors located at or below finished grade with a ceiling height of less than 1.2 m;
- (h) covered verandas or porches, provided that:
  - (i) the portion facing the street, side property line or rear property line, park or school, is open or protected by partial walls or guard rails, which conform to the height minimum specified in the Building By-law, and
  - (ii) the total excluded area, combined with the balcony and sun deck exclusions permitted in section 4.7.5 (a) of this schedule, does not exceed 16% of the permitted floor area for multiple dwellings and 13% of the permitted floor area for all other uses, and

- (iii) the ceiling height, excluding roof structures, of the total area being excluded does not exceed 3.1 m measured from the porch floor;
- (i) portions of exterior walls contributing to thermal and building envelope performance, in accordance with section 10.33 of this by-law; and
- (j) above grade floor area built as open to below, designed in combination with venting skylights, opening clerestory windows or other similar features which, in the opinion of the Director of Planning, reduce energy consumption or improve natural light and ventilation to a maximum exclusion of one percent of permitted floor area.

#### **4.8 Site Coverage and Impermeability**

- 4.8.1 The maximum site coverage for buildings is 45% of the site area, except that, for multiple dwelling and freehold rowhouse, the maximum site coverage for all buildings is 55% of the site area.
- 4.8.2 Site coverage for buildings must be based on the projected area of the outside of the outermost walls of all buildings and includes carports, but excludes steps, eaves, balconies and sun decks.
- 4.8.3 The area of impermeable materials, including site coverage for buildings, must not exceed 70% of the total site area, except that for multiple dwelling, the Director of Planning may increase the area of impermeable materials, provided that the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.
- 4.8.4 For the purposes of section 4.8.3 of this schedule:
  - (a) the following are considered impermeable: the projected area of the outside of the outermost walls of all buildings including carports, covered porches and entries, asphalt, concrete, brick, stone, and wood; and
  - (b) the following are considered permeable: gravel, river rock less than 5 cm in size, wood chips, bark mulch, wood decking with spaced boards and other materials which, in the opinion of the Director of Planning, have fully permeable characteristics when placed or installed on grade with no associated layer of impermeable material (such as plastic sheeting) that would impede the movement of water directly to the soil below.

#### **4.9 [Deleted — see Parking by-law.]**

#### **4.10 Horizontal Angle of Daylight**

- 4.10.1 All habitable rooms in buildings containing 3 or more dwelling units, not including secondary dwelling units, must have at least 1 window on an exterior wall which complies with the following:
  - (a) the window must be located so that a plane or planes extending from the window and formed by an angle of 50 degrees, or 2 angles with a sum of 70 degrees, must be unobstructed over a distance of 24 m; and
  - (b) the plane or planes must be measured horizontally from the centre of the bottom of the window.
- 4.10.2 For the purpose of section 4.10.1 of this schedule, the following are considered as obstructions:
  - (a) the theoretically equivalent buildings located on any adjoining sites in any R District in a corresponding position by rotating the plot plan of the proposed building 180 degrees around a horizontal axis located on the property lines of the proposed site;



- (b) part of the same building including permitted projections;
  - (c) accessory buildings located on the same site as the principal building; and
  - (d) the maximum size building permitted under the appropriate C or M district schedule if the site adjoins a C or M site.
- 4.10.3 For the purposes of section 4.10.1 of this schedule, the following are not considered as habitable rooms:
- (a) bathrooms; and
  - (b) kitchens, unless the floor area is greater than 10% of the total floor area of the dwelling unit, or 9.3 m<sup>2</sup>, whichever is the greater.
- 4.10.4 The Director of Planning may relax the horizontal angle of daylight requirement of section 4.10.1 of this schedule, provided:
- (a) a minimum distance of 2.4 m of unobstructed view is maintained; and
  - (b) the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.

**4.11 Dedication of Land for Lane Purposes**

- 4.11.1 Where a site does not abut a lane, or abuts a lane which is less than 6.1 m in width, a portion of the site, as determined by the City Engineer, to a maximum of 3.1 m, shall be dedicated for lane purposes.
- 4.11.2 Where land is dedicated pursuant to section 4.11.1, it shall be deemed not to reduce the site area for the purpose of calculating floor space ratio.

**4.12 - 4.14 (Reserved)**

**4.15 Acoustics**

- 4.15.1 A development permit application for a dwelling use in the RM-7N District requires evidence in the form of a report and recommendations prepared by persons trained in acoustics and current techniques of noise measurements, demonstrating that the noise levels in those portions of the dwelling units listed below, do not exceed the noise levels expressed in decibels set opposite such portions of the dwelling units. For the purposes of this section the noise level is the A-weighted 24-hour equivalent (Leq) sound level and will be defined simply as the noise level in decibels.

Portions of dwelling units	Noise levels (Decibels)
Bedrooms	35
Living, dining, recreation rooms	40
Kitchen, bathrooms, hallways	45

**4.16 Building Depth and Width**

- 4.16.1 For all dwelling uses, the maximum distance between the required minimum front yard and the rear of a building is 40% of the site depth, measured prior to any required lane dedication.
- 4.16.2 Notwithstanding section 4.16.1 of this schedule, the Director of Planning may increase the maximum distance between the required minimum front yard and the rear of a multiple dwelling if the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.

- 4.16.3 Projections permitted in front yards pursuant to section 4.4.4 of this schedule must not be included in the calculation of building depth.
- 4.16.4 Notwithstanding section 4.16.1 of this schedule, the Director of Planning may permit an infill one-family dwelling or another principal building in the rear yard if the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.
- 4.16.5 On sites 24 m and wider, the maximum building width for a multiple dwelling is 22 m, except that the Director of Planning may increase the maximum building width, provided the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.

#### **4.17 External Design**

- 4.17.1 An infill one-family dwelling or another principal building located in the rear yard of a site, must be a minimum distance of 4.9 m, measured across the width of the site, from any other dwelling use on the site, except that the Director of Planning may decrease the minimum distance for an infill one-family dwelling, provided the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.
- 4.17.2 Where a site has more than one multiple dwelling building, the exterior wall of each multiple dwelling building must be a minimum of 2.4 m from the closest portion of the exterior wall of any other multiple dwelling building on the site.
- 4.17.3 Where a site has more than one building containing freehold rowhouses, the exterior wall of each building must be a minimum distance of 2.4 m from the closest portion of the exterior wall of any other building containing freehold rowhouses on the site.
- 4.17.4 For the purpose of this section 4.17, a main entrance means a door facing a street not being a lane, which is visible from the street and is located at or within 1.8 m of grade, or connected to grade by stairs or a ramp.
- 4.17.5 In a two-family dwelling or a two-family dwelling with secondary suite on a site with one principal building:
- there must be one main entrance to each principal dwelling unit;
  - there must be a covered verandah or porch at each main entrance, with a minimum width and depth of 1.6 m;
  - all roofs except for dormer roofs must be hip, gable or a combination of both forms, and must have a minimum slope of 7:12;
  - dormer roofs must be gable, hip or shed in form and have a minimum slope of 4:12; and
  - the maximum total width of dormer roofs provided on a half storey above the second storey must comply with the following table:

<b>Dormer Orientation</b>	<b>Maximum Total Dormer Width</b>
Rear yard	40% of width of elevation of storey below
Interior side yard	25% of width of elevation of storey below
Street or flanking lane	30% of width of elevation of storey below

- 4.17.6 Exterior windows in a secondary suite must have:
- a minimum total glazing area of 10% of the total floor area of the room, in each of the kitchen, living room and dining room; and
  - a minimum total glazing area of 5% of the total floor area of the room, in all other rooms except bathrooms and laundry rooms.

#### **4.18 Dwelling Unit Density**

- 4.18.1 For multiple dwelling and freehold rowhouse, the total number of dwelling units, excluding lock-off units, must not exceed:
- (a) for development up to and including 0.90 floor space ratio, 100 units per hectare of site area; or
  - (b) for development over 0.90 and up to and including 1.20 floor space ratio, 132 units per hectare of site area.
- 4.18.2 Where the calculation of dwelling units per hectare results in a fractional number, the number must be rounded down.

#### **4.19 Number of Buildings on Site**

- 4.19.1 Notwithstanding section 10.1 of this by-law, the Director of Planning may permit a second principal building in conjunction with a one-family dwelling, a one-family dwelling with secondary suite, a two-family dwelling or a two-family dwelling with secondary suite on a site, provided:
- (a) the site meets one of the following criteria:
    - (i) the rear or side property line of the site abuts a park or school site, with or without the intervention of a lane,
    - (ii) the site is a corner site, or
    - (iii) the lot depth is more than 52 m;
  - (b) the principal building situated in the rear yard of the site contains no more than one dwelling unit;
  - (c) the total number of dwelling units on the site does not exceed 3, excluding any secondary suites; and
  - (d) the Director of Planning first considers the intent of this schedule and all applicable Council policies and guidelines.
- 4.19.2 Notwithstanding section 10.1 of this by-law, the Director of Planning may permit more than one multiple dwelling or freehold rowhouse building on a site, if:
- (a) the site has a minimum site area of 703 m<sup>2</sup>; and
  - (b) the Director of Planning first considers the intent of this schedule and all applicable policies and guidelines.

### **5 Relaxation of Regulations**

- 5.1 The Director of Planning may relax the minimum site area requirements of section 4.1 of this schedule and the minimum frontage provisions of section 4.2 of this schedule with respect to any of the following developments, if the lot was on record in the Land Title Office for Vancouver prior to May 15, 2013:
- (a) two-family dwelling;
  - (b) two-family dwelling with secondary suite;
  - (c) infill one-family dwelling in conjunction with the retention of a building existing on the site prior to January 1, 1940; and
  - (d) multiple dwelling with no more than three dwelling units,
- if the Director of Planning first considers the quality and livability of the resulting units, the effect on neighbouring properties and all applicable Council policies and guidelines.

